

# Neat Video quick start guide

## 1. Installing the plug-in

### To install the Neat Video plug-in

1. Download (from the Neat Video website: <http://www.neatvideo.com/download.html> ) one of the DMG packages that matches your host application (Intel or PowerPC version of OpenFX version of Neat Video);
2. Click the downloaded file to mount the DMG volume;
3. In the mounted volume, double-click *NeatVideoOFX.Intel.pkg* (or *NeatVideoOFX.PowerPC.pkg*) to start the installer;
4. Follow the steps of the installer wizard to complete the installation process; (you may be prompted to enter the Name / Password of the OSX administrator account);
5. Restart the host application and find Neat Video | Reduce noise in the list of video effects / filters.

If Neat Video has **not** become available in the host application after restart, please contact Neat Video support for assistance.

## 2. Running Neat Video on a sample video clip

There is a test-kit prepared to help you start using Neat Video. You can download the test-kit from the Neat Video web page: <http://www.neatvideo.com/files/testkit.zip> (2 MB). Having downloaded, unzip it to a new folder on the hard disk.

The test-kit includes a sample video clip: the *SampleClip.mpg* file. This clip is a part of typical video clip captured by a digital camcorder. Detailed information about the sample clip is available in the *SampleClipInfo.txt* file.

Please start the host application and go through the stages below to see how Neat Video can improve the clip:

### 2.1. Stage I. Create a new project with sample clip

#### 1. Create a new project

Use the host tools to set up a project and/or sequence with the following parameters (when the corresponding settings are adjustable):

- Frame size: 640x480 pixels
- Frame rate: 30 fps
- Field order: Progressive scan
- Pixel aspect ratio: 1.0 (square pixels)

#### 2. Add the sample clip file to the project

- ➔ Use the host tools to import the sample clip and insert it into the timeline.

#### 3. Check the sample clip in preview

- ➔ Use the host preview window to check how the clip looks like.

You will see that there is some noise in the clip. The task of Neat Video is to reduce this noise.

### 2.2. Stage II. Add Neat Video to the clip

- ➔ Use the host tools to add the Neat Video (Reduce Noise) effect to the sample clip in the timeline.

## 2.3. Stage III. Configure Neat Video

### 1. Open Neat Video plug-in window

- ➔ Open the Neat Video plug-in window using the Options button in the effect's settings panel.

The Neat Video plug-in window will open and show the currently selected frame from the clip.

### 2. Load noise profile

To reduce noise in this frame and in the whole clip, Neat Video generally needs a noise profile describing the noise properties of the clip. We have prepared such a noise profile in advance. The profile is supplied with the test-kit in the *SampleProfile.dnp* file. Using the noise profile, Neat Video can efficiently reduce the noise in the clip.



- ➔ 1. In the Device Noise Profile tab:  click  Load Profile (the Load Profile button);

2. In the Open Device Noise Profile dialog, navigate to the folder where the sample device noise profile has been unzipped and select the *SampleProfile.dnp* file.

Neat Video will load the noise profile and will then be ready to filter the sample clip.

Usually, you would adjust the filter settings at this point. To make things easier for the first run, we have prepared a sample preset file that stores 'good' filter settings suitable for the sample clip.


### 3. Load filter preset

- ➔ 1. Switch to the Noise Filter Settings tab:  and click  (the Load Filter Preset button) in the Filter Settings box;

2. In the Load Filter Preset dialog, navigate to the folder where the sample filter preset has been unzipped and select the *SamplePreset.nfp* file.

Now the sample filter preset is loaded and the filter settings are adjusted to process the sample clip.

### 4. Apply the changes

- ➔ Click  in the bottom of the plug-in window.

The plug-in will close its main window and will save the changed device noise profile and filter preset in the project your work with.

Keep the default values of the Temporal filter settings in the effect's settings panel for now.

## 2.4. Stage IV. Render the clip

- ➔ Use the host tools to render the whole clip.

This will automatically apply Neat Video noise reduction to the sample clip so that you could evaluate the filtration and adjust the filter settings if necessary. You will see that the noise in the resulting clip is significantly reduced while the true details are preserved. You can also find that the resulting noise-free clip can be compressed better (the file size is smaller) than the original noisy clip.

The sample noise profile and filter preset supplied with the test-kit are suitable only for the sample clip and similar clips produced by the same capturing device working in the same or similar mode. Neat Video can perform noise reduction on video clips captured or acquired by any other devices working in any mode. To be able to do that Neat Video needs device noise profiles that describe the noise characteristics of those devices. With Neat Video you can easily build these profiles yourself. The software can completely automatically build a profile once you give it a suitable frame from a clip.